

SMALL CENTRIFUGES

24 x Capillaries

Z 207 H

Due to its compact design, the hematocrit centrifuge Z 207 H can also be used in even the smallest laboratories. It is equipped with a hematocrit rotor for 24 x capillaries. The innovative control panel with touch function is a particular highlight.



TECHNICAL SPECIFICATIONS

MAX. SPEED	13,000 rpm
MAX. RCF	16,058 xg
MAX. VOLUME	24 x capillaries
SPEED RANGE	200 – 13,000 rpm
RUNNING TIME	59 min 50 s / 10 s increments or 99 h 59 min / 1 min increments
DIMENSIONS (W X H X D)	28 cm x 24 cm x 35 cm
WEIGHT	12.5 kg
POWER CONSUMPTION	150 W

ORDER NUMBERS

331.00 P01 – Z 207 H, 230 V/50 – 60 Hz, incl. 24 x capillary Rotor

331.00 P02 – Z 207 H, 120 V/50 – 60 Hz, incl. 24 x capillary Rotor

SPECIFICATIONS

- Microprocessor control with LCD display
- Electromagnetic lid lock
- Quick access to the samples
- Active imbalance detection and shutdown
- Air cooling
- Short acceleration and deceleration times
- Noise level < 60 dBA at max. speed
- Easy removal of the rotor
- Manufactured in accordance with international safety guidelines, e.g. IEC 61010
- Colour-based visual display of the operating state
- Sleep mode

ENCLOSED ROTOR INCLUSIVE LID

Order number: 221.60 V01

MAX. SPEED: 13,000 rpm

Max. RCF: 16,058 xg

Max. Radius: 8.6 cm



Hematocrit rotor for 24 x capillaries

Angle: 90°