## Cole-Parmer®

Cole-Parmer® Industrial Flame Photometer

-FF-200

- Designed for industrial analysis
- Supplied with Na, K, Li, Ba and Ca filters
- Low temperature, single channel
- Flame failure safety system
- Operates with propane, butane, natural gas or LPG
- 3 year warranty





#### **Technical Specification**

Specification	FF-200				
Parameter	FF-200				
Range	0 to 199.9ppm				
Limits of detection Na	0.2ppm				
К	0.2ppm				
Li	0.25ppm				
Ca	15ppm				
Ba	30ppm				
Reproducibility	<1% coefficient of variation for 20 consecutive samples using 10ppm Na set to read 50				
Linearity	< 2% error when 3ppm Na/K and 5ppm Li are set to read 100				
Stability	< 2% drift over 5min when continuously aspirating 10ppm sample set to 50.0. Specificity Interference from Na/K and Li equal in concentration to test element will be <0.5%				
Recorder output	Nominal 1.00V for a reading of 100.0				
Electrical supply	90-125V or 190-250V @50/60Hz				
Air supply	Moisture and oil free, 6 litre/min @ 14psi				
Fuel	Propane, butane, natural gas or LPG				
Size (w x d x h)	420 x 360 x 300mm				
Weight	8kg				

# Cole-Parmer® Industrial Flame Photometer - FF-200

The Cole-Parmer® FF-200 is a low temperature, single channel flame photometer that is designed for the routine determination of sodium, potassium, calcium, barium and lithium concentrations.

The flame failure safety system makes these products ideal for use in industrial and educational environments. The use of fine and coarse sensitivity controls allows for accurate measurements each and every time.



### **Ordering Information**

Description	Ordering Number	Series No.	Model No.	Legacy Sku.
Cole-Parmer FF-200 (230V) Economical Flame Photometer, 230V	83055-05	FF-200	FF-200D-I	500701

### coleparmer.com

USA: +1.800.323.4340 +1.847.549.7600 Canada: +1.800.363.5900 China: +86.21.5109.9909 France: +33 (0) 1486 37800 Germany: +49 (0) 9377 92030 India: +1.800.266.1244 Italy: +39 (0) 1313 89513 UK: +44 (0) 1480 272279

All other countries: +1.847.549.7600

