

SMALL CENTRIFUGES

6 x 50 ml

Z 206 A

Up to 12 x 15 ml sample tubes (also conical) can be used in the Z 206 A. Adapters are available for smaller tube dimensions and blood collection systems. For larger volumes, a fixed-angle rotor for 6 x 50 ml tubes (conical and round bottom) is also available.

TECHNICAL SPECIFICATIONS

MAX. SPEED	6,000 rpm
MAX. RCF	4,467 xg
MAX. VOLUME	6 x 50 ml
SPEED RANGE	200–6,000 rpm in 50 rpm increments / 10 rcf increments
RUNNING TIME	59 min 50 s / 10 s increments or 99 h 59 min / 1 min increments
DIMENSIONS (W X H X D)	28 cm x 26 cm x 37 cm
WEIGHT	12 kg



ORDER NUMBERS

306.00 V01 – Z 206 A, 230 V/50 – 60 Hz/100 W

306.00 V02 – Z 206 A, 120 V/50 – 60 Hz/100 W



Main rotor



Max. volume: 12 x 15 ml
Round bottom and conical
Order number: 221.54 V01



Max. volume: 6 x 50 ml
Round bottom and conical
Order number: 221.55 V01

The respective max. capacities of the rotors are shown in the tables. Naturally, adapters are available for smaller volumes. Detailed information can be found on our web page www.bilmар.com.tr. If you cannot find the required adapter, we will gladly make a custom adapter for you.

ROTORS

MAX. VOLUME	MAX. SPEED	RCF VALUE	ORDER NUMBERS	ANGLE
6 x 50 ml	6,000 rpm	4,427 xg	221.55 V01	40°
12 x 15 ml	6,000 rpm	4,427 xg	221.54 V01	32°
18 x 1.5/2.0 ml	6,000 rpm	2,938 xg	220.95 V06	45°
6 x 5.0 ml	4,000 rpm	1,896 xg	220.68 V04	0–90°
4 x 4.0–7.0 ml	6,000 rpm	4,467 xg	221.37 V01	0–77°