

ROTORS

| MAX. VOLUME | MAX. SPEED | RCF VALUE | ORDER NUMBER | ANGLE |
|--------------------|------------|-----------|--------------|---------|
| 4 x 1,000 ml* | 4,600 rpm | 5,203 xg | 221.65 V20 | 0 – 90° |
| 4 x 750 ml* | 4,500 rpm | 4,346 xg | 221.36 V20 | 0 – 90° |
| 4 x 500 ml | 8,000 rpm | 10,374 xg | 221.51 V20 | 24° |
| 6 x 250 ml | 8,000 rpm | 10,016 xg | 221.21 V20 | 28° |
| 10 x 50 ml conical | 10,500 rpm | 16,022 xg | 221.52 V20 | 38° |

* hermetically sealed

EXAMPLE ROTORS



Max. volume: 4 x 1,000 ml
Order number: 221.65 V20
Hermetically sealed



Max. volume: 4 x 500 ml
Order number: 221.51 V20



Max. volume: 6 x 250 ml
Order number: 221.21 V20

The respective max. capacities of the rotors are shown in the tables. Naturally, adapters are available for smaller volumes.
Detailed information can be found on our homepage www.bilmar.com.tr
If you cannot find the required adapter, we will gladly make a custom adapter for you