## 9500

### Bench Dissolved Oxygen Meter

The 9500 is a research meter designed for use in a number of applications including fish farming/breeding, all forms of aquaculture, environmental analysis, pollution control and effluent management. The 9500 includes powerful data logging capabilities with the ability to store 250  $DO_2$  readings either manually, at timed intervals or on alarmed events. The 9500 also includes full support for the B.O.D<sub>5</sub> day test protocol and has the ability to store up to 20 B.O.D data sets, each with up to 10 samples.

#### **Technical Specification**



#### **Key Features**

- Results as % air saturation, % oxygen or mg/l
- Automatic zeroing and calibration

JENWAY

- Atmospheric pressure and salinity correction
- B.O.D<sub>5</sub> measurement and calculation
- RS232 for connection to printer or PC and IrDA for cableless printing option

Range	0 to 199%	9500 DO, Meter
	0 to 25.0%	- Meter
	0 to 19.99mg/l	EST J CAL - CAL
Resolution	1%, 0.1%, 0.01mg/l	CIR - L
Accuracy	±2% within 10°C of calibration	570
	temperature	
Temperature		
Range	-10 to 60°C	9500
Resolution	0.1°C	Part code: 950 201
Accuracy	±0.5°C	Part code: 950 201
ATC/Manual	0 to 60°C	T
Other		
Data Logging	250 readings storage and 20 B.O.D sets	
	(10 samples per set)	
Clock	24 hour, hrs/min/sec or day/month/	
	year, leap year corrected	
GLP	Calibration reminder	
	Alarm outputs	JENWAY
	Security code protected user data	
Outputs	Analogue, RS232 and IrDA	19.5
Connector	7-pin DIN	
Power	9V AC ±10% @ 50/60Hz	9500 DO, Meter
Size (I x w x d), mm	210 x 250 x 55	T - CAL - O
Weight, g	850	esc and L

#### **Ordering Information**

Part Code	Descr	iptior	1 I					
950 201	9500	diss	olved	oxygen	met	er su	pplied	with
	DO2	pr	obe	with	ATC	(52	2	023B),
	electrode holder		(903	300),	spare	mem	branes,	
	KCI	fill solut		ution,	zero	calibration		salts,
	adapter bush and European 230V power supply (021 031)						21 031)	

# bilm@r

BİLMAR BİLİMSEL ARAŞTIRMA VE MÜHENDİSLİK ANONİM ŞİRKETİ web page : www.bilmar.com.tr e-mail : bilkim@bilmar.com.tr